

屋内照明器具特性

品番(品名)	LGD1038L	
光源	LED2700_70_150 x1	150.0 lm
管理番号	K0147639(0)DB1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		下方光束 102%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	91	86	83	81	91	86	83	81	90	86	83	81	89	85	83	81	80
	中	0.63	0.8	96	92	89	87	95	91	89	87	94	91	88	86	93	90	88	86	85
	否	0.56	1.0	99	95	92	90	98	95	92	90	97	94	91	90	95	93	91	89	88
下方投影面積	等価発光面積	cm ²	1.25	101	98	95	93	100	97	95	93	99	96	94	93	97	95	93	92	91
			1.5	103	100	97	96	102	99	97	95	100	98	96	95	99	97	95	94	92
取付高さ	器具間隔最大限		2.0	104	102	100	98	104	101	100	98	102	100	98	97	100	99	97	96	95
	横方向(A)	縦方向(B)	2.5	106	104	102	100	105	103	101	100	103	101	100	99	101	100	99	98	96
Hm	0.50Hm	0.50Hm	3.0	106	105	103	102	105	104	102	101	103	102	101	100	102	101	100	99	97
			4.0	107	106	105	104	106	105	104	103	104	103	102	101	101	102	101	101	100
			5.0	108	107	106	105	107	106	105	104	105	104	103	102	103	102	101	101	99
			7.0	108	108	107	106	107	107	106	105	105	104	104	103	103	102	102	102	99
			10.0	109	108	108	107	108	107	107	106	106	105	105	104	104	103	103	103	100

