

# 屋内照明器具特性

品番(品名)	LGD1038N																
光源	LED5000_70_166 x1 166.0lm																
管理番号	K0147639(0)DB1																
BZ分類	BZ1																

器具効率	102%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	102%		10%				10%				10%				10%				0%	
		室指数	照明率 ( X0.01 ) ZCM																	
保守率	良	0.67	0.6	91	86	83	81	91	86	83	81	90	86	83	81	89	85	83	81	80
	中	0.63	0.8	96	92	89	87	95	91	89	87	94	91	88	86	93	90	88	86	85
	否	0.56	1.0	99	95	92	90	98	95	92	90	97	94	91	90	95	93	91	89	88
下方投影面積	cm <sup>2</sup>	1.25	101	98	95	93	100	97	95	93	99	96	94	93	97	95	93	92	91	
		1.5	103	100	97	96	102	99	97	95	100	98	96	95	99	97	95	94	92	
等価発光面積	cm <sup>2</sup>	2.0	104	102	100	98	104	101	100	98	102	100	98	97	100	99	97	96	95	
		2.5	106	104	102	100	105	103	101	100	103	101	100	99	101	100	99	98	96	
取付高さ	器具間隔最大限		3.0	106	105	103	102	105	104	102	101	103	102	101	100	102	101	100	99	97
	H <sub>m</sub>	0.50H <sub>m</sub>	0.50H <sub>m</sub>	4.0	107	106	105	104	106	105	104	103	104	103	102	101	102	101	100	98
			5.0	108	107	106	105	107	106	105	104	105	104	103	102	103	102	101	101	99
			7.0	108	108	107	106	107	107	106	105	105	104	104	103	103	102	102	102	99
			10.0	109	108	108	107	108	107	107	106	106	105	105	104	104	103	103	103	100

