

屋内照明器具特性

品番(品名)	LGD1039L	
光源	LED2700_70_123 x1	123.0lm
管理番号	K0147639(0)DB1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%					
	上方光束 0%		下方光束 102%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
室指数	照明率 (X0.01)																			ZCM				
保守率	良 0.67	中 0.63	否 0.56	0.6	91	86	83	81	91	86	83	81	90	86	83	81	89	85	83	81	80			
	1.0			99	95	92	90	98	95	92	90	97	94	91	90	95	93	91	89	88	85			
	1.25			101	98	95	93	100	97	95	93	99	96	94	93	97	95	93	92	91	91	88		
下方投影面積 等価発光面積	cm ²	1.5	103	100	97	96	102	99	97	95	100	98	96	95	99	97	95	94	92	92				
		2.0	104	102	100	98	104	101	100	98	102	100	98	97	100	99	97	96	95	95				
取付高さ Hm	器具間隔最大限		Hm	0.50Hm	Hm	0.50Hm	2.5	106	104	102	100	105	103	101	100	103	101	100	99	101	100	99	98	96
	3.0	106					105	103	102	105	104	102	101	103	102	101	100	102	101	100	99	97	97	97
4.0	107	106	105	104	106	105	104	103	104	103	102	101	101	102	101	100	101	100	98	98	98	97	96	
5.0	108	107	106	105	107	106	105	104	105	104	103	102	101	103	102	101	101	101	99	99	99	98	97	
7.0	108	108	107	106	107	107	106	105	105	104	103	102	101	103	102	101	101	101	99	99	99	98	97	
10.0	109	108	108	107	108	107	107	106	106	105	104	103	102	104	103	102	102	102	100	100	100	99	98	

