

屋内照明器具特性

品番 (品名)	LGD1100									
光源	LED5000_70_460 x1					460.0 lm				
管理番号	K0154589(0)D 1									
BZ分類	BZ4/0.7/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%			
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床	10%				10%				10%				10%				0%			
室指数			照明率 (X0.01)																			
保守率	良	0.67	0.6	61	50	43	38	60	49	42	37	58	48	42	37	56	47	41	37	35		
	中	0.63	0.8	72	61	54	49	70	61	54	49	68	59	53	49	66	58	53	49	47		
	否	0.56	1.0	78	69	63	58	77	68	62	57	74	67	61	57	72	66	61	57	55		
			1.25	84	76	70	65	83	75	70	65	80	74	69	65	78	72	68	64	62		
下方投影面積	cm ²		1.5	88	81	75	71	87	80	75	71	84	78	74	70	82	77	73	69	67		
	等価発光面積		2.0	93	87	83	79	92	86	82	78	89	85	81	77	87	83	79	77	74		
取付高さ	器具間隔最大限		2.5	96	91	87	84	95	90	86	83	92	88	85	82	90	87	84	81	79		
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	90	87	94	91	88	86	92	89	87	84	82		
Hm	1.24Hm	1.24Hm	4.0	101	98	95	92	100	97	94	91	97	94	92	90	95	92	91	89	86		
			5.0	102	100	97	95	101	99	96	94	99	96	95	93	96	94	93	91	89		
			7.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	96	94	92		
			10.0	105	104	103	101	104	103	102	100	102	101	100	99	99	99	98	97	94		

