

屋内照明器具特性	
品番 (品名)	LGC31601
光源	LED6200_70_4299 ×1 4299.0lm
管理番号	K0164431(0)D 1
BZ分類	BZ6/0.7/BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																	ZCM
保守率		良 中 否	0.63	0.6	0.6	53	40	32	26	51	39	31	26	48	37	30	25	44	35	29	25	22
			0.6	0.8	63	50	42	36	60	49	41	36	56	47	40	35	53	45	39	34	31	
			0.56	1.0	69	58	50	43	67	56	49	43	63	54	47	42	59	51	45	41	37	
				1.25	75	65	57	51	73	63	56	50	68	60	54	49	64	57	52	47	44	
下方投影面積 等価発光面積		cm ² cm ²		1.5	79	70	62	57	77	68	61	56	72	65	59	54	68	62	57	52	48	
				2.0	85	77	71	65	83	75	69	64	78	72	66	62	73	68	64	60	56	
				2.5	89	82	76	71	86	80	75	70	82	76	72	67	77	73	69	65	61	
				3.0	92	85	80	75	89	83	78	74	84	79	75	72	80	76	72	69	64	
Hm	1.42Hm	1.42Hm		4.0	95	90	86	82	92	88	84	80	88	84	80	77	83	80	77	74	70	
				5.0	97	93	89	86	94	91	87	84	90	87	84	81	85	83	80	78	73	
				7.0	99	96	93	91	97	94	91	89	92	90	88	86	88	86	84	82	77	
				10.0	101	99	97	95	99	97	95	93	94	93	91	89	90	89	87	86	80	

