

屋内照明器具特性

品番 (品名)	LGC31602									
光源	LED6200_70_4000 x1 4000.0 lm									
管理番号	K0164946(0)D 1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	16%	床	10%				10%				10%				10%				0%				
下方光束	84%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	53	40	32	27	51	39	32	26	47	37	30	25	43	35	29	24	21			
	中	0.6	0.8	62	50	42	36	60	49	41	35	55	46	39	34	51	43	37	33	29			
	否	0.56	1.0	68	57	49	43	66	55	48	42	61	52	46	41	56	49	43	39	35			
			1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	55	49	45	41			
下方投影面積			1.5	78	69	61	56	75	67	60	54	70	63	57	52	65	59	54	50	45			
			2.0	84	76	69	64	81	74	67	62	75	69	64	60	70	65	61	57	52			
取付高さ	器具間隔最大限		2.5	88	81	75	70	84	78	73	68	79	73	69	65	73	69	65	62	56			
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	87	81	76	72	81	76	72	69	76	72	68	65	59			
Hm	1.30Hm	1.30Hm	4.0	93	88	84	80	90	86	82	78	84	81	77	74	79	76	73	70	64			
			5.0	95	91	87	84	92	89	85	82	87	83	80	78	81	78	76	74	67			
			7.0	98	95	92	89	95	92	89	86	89	87	84	82	84	82	80	78	71			
			10.0	100	97	95	93	97	95	92	90	91	89	87	86	86	84	83	81	74			

