

# 屋内照明器具特性

品番 (品名)	LGC41603									
光源	LED6200_70_4650 x1					4650.0 lm				
管理番号	K0164944(0)D 1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 5%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				下方光束 95%	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	54	41	33	27	52	40	32	27	49	38	31	26	46	37	31	26	24	
	中	0.6	0.8	63	51	43	37	62	50	42	37	58	48	41	36	55	47	40	36	33	
	否	0.56	1.0	70	59	51	44	68	58	50	44	64	55	48	43	61	53	47	42	40	
			1.25	76	66	58	52	74	64	57	51	70	62	56	50	67	60	54	49	46	
下方投影面積	c m <sup>2</sup>		1.5	80	71	64	58	78	70	63	57	74	67	61	56	71	64	59	55	51	
	等価発光面積		c m <sup>2</sup>	2.0	86	78	72	66	84	77	71	65	80	74	68	64	76	71	66	63	59
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	81	76	71	84	78	74	70	80	75	71	68	64	
	H m	1.40 H m	縦方向 ( B )	3.0	93	87	81	77	90	85	80	76	86	82	78	74	83	79	75	72	68
	1.40 H m	1.41 H m	横方向 ( A )	4.0	96	91	87	83	94	89	85	82	90	86	83	80	86	83	80	77	74
				5.0	98	94	90	87	96	92	89	86	92	89	86	83	88	86	83	81	77
				7.0	100	97	94	92	98	96	93	90	95	92	90	88	91	89	87	85	81
				10.0	102	100	98	96	100	98	96	94	97	95	93	92	93	92	90	89	85

