

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 6 1									
光源	LED2700_70_265 ×1					265.0 l m				
管理番号	K0171393 ( 0 ) DB 1									
B Z 分類	B Z 6 / 1.4 / B Z 5 / 1.8 / B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	51 %	反射率	床		10 %		10 %		10 %		10 %		10 %		10 %		0 %			
下方光束	49 %		室指数																	
保守率	良 0.63 中 0.6 否 0.56	照明率 ( X 0.01 )																	Z C M	
		0.6	48	37	29	24	44	34	27	23	37	29	24	20	30	24	20	17	12	
下方投影面積	c m <sup>2</sup>	1.25	68	59	52	46	63	55	48	43	53	46	41	37	44	39	35	32	23	
		1.5	72	64	57	51	67	59	53	48	56	50	45	42	46	42	38	35	25	
等価発光面積	c m <sup>2</sup>	2.0	78	70	64	59	72	65	60	55	61	56	51	48	50	46	43	41	29	
		2.5	81	75	69	64	75	69	64	60	63	59	55	52	53	49	47	44	32	
取付高さ	器具間隔最大限		3.0	84	78	73	69	77	72	68	64	65	62	58	55	54	52	49	34	
	横方向 ( A )	縦方向 ( B )	4.0	87	82	78	74	80	76	73	69	68	65	62	60	57	55	52	37	
H m	1.37 H m	1.29 H m	5.0	89	85	81	78	82	79	76	73	70	67	65	63	58	56	55	39	
			7.0	91	88	85	83	84	82	79	77	72	70	68	66	60	59	57	41	
			10.0	93	90	88	86	86	84	82	81	74	72	71	69	62	61	60	43	

