

# 屋内照明器具特性

品番 (品名)	LGD1037L	
光源	LED2700_70_287 ×1	287.0 lm
管理番号	K0147637(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.67	0.6	84	78	74	72	84	78	74	71	82	77	74	71	81	77	73	71	70	
	中 0.63		0.8	91	85	82	79	90	85	81	79	88	84	81	78	87	83	80	78	77
	否 0.56		1.0	94	90	86	84	93	89	86	83	92	88	85	83	90	87	85	83	81
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	97	93	90	88	96	93	90	87	95	91	89	87	93	90	88	86	85	
		1.5	99	96	93	91	98	95	92	90	97	94	91	90	95	93	91	89	87	
取付高さ	器具間隔最大限		2.5	103	101	99	97	102	100	98	96	100	98	97	95	98	97	96	94	92
	横方向 (A)	縦方向 (B)	3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94
Hm	0.50Hm	0.50Hm	4.0	106	104	102	101	104	103	102	100	102	101	100	99	100	99	98	98	95
			5.0	106	105	104	102	105	104	103	102	103	102	101	100	101	100	99	99	96
			7.0	107	106	105	104	106	105	104	103	104	103	102	102	101	101	100	100	97
			10.0	108	107	106	106	107	106	105	105	104	104	103	103	102	102	101	101	98

