

# 屋内照明器具特性

|        |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番(品名) | LGD1039N                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源     | LED5000_70_134 x1 134.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号   | K0147639(0)DB1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類   | BZ1                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                 |        |                   |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|--------|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 102%            | 天井     | 80%               |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |                 |        | 70                | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 0%              | 反射率    | 壁                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 下方光束   | 102%            |        | 床                 | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
|        |                 | 室指数    | 照明率 ( X0.01 ) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良               | 0.67   | 0.6               | 91  | 86  | 83  | 81  | 91  | 86  | 83  | 81  | 90  | 86  | 83  | 81  | 89  | 85  | 83  | 81  | 80  |
|        | 中               | 0.63   | 0.8               | 96  | 92  | 89  | 87  | 95  | 91  | 89  | 87  | 94  | 91  | 88  | 86  | 93  | 90  | 88  | 86  | 85  |
|        | 否               | 0.56   | 1.0               | 99  | 95  | 92  | 90  | 98  | 95  | 92  | 90  | 97  | 94  | 91  | 90  | 95  | 93  | 91  | 89  | 88  |
| 下方投影面積 | cm <sup>2</sup> | 1.25   | 101               | 98  | 95  | 93  | 100 | 97  | 95  | 93  | 99  | 96  | 94  | 93  | 97  | 95  | 93  | 92  | 91  |     |
|        |                 | 1.5    | 103               | 100 | 97  | 96  | 102 | 99  | 97  | 95  | 100 | 98  | 96  | 95  | 99  | 97  | 95  | 94  | 92  |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0    | 104               | 102 | 100 | 98  | 104 | 101 | 100 | 98  | 102 | 100 | 98  | 97  | 100 | 99  | 97  | 96  | 95  |     |
|        |                 | 2.5    | 106               | 104 | 102 | 100 | 105 | 103 | 101 | 100 | 103 | 101 | 100 | 99  | 101 | 100 | 99  | 98  | 96  |     |
| 取付高さ   | 器具間隔最大限         |        | 3.0               | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 101 | 103 | 102 | 101 | 100 | 102 | 101 | 100 | 99  | 97  |
|        | 横方向(A)          | 縦方向(B) | 4.0               | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 98  |     |
| Hm     | 0.50Hm          | 0.50Hm | 5.0               | 108 | 107 | 106 | 105 | 107 | 106 | 105 | 104 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 99  |
|        |                 |        | 7.0               | 108 | 108 | 107 | 106 | 107 | 107 | 106 | 105 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 102 | 99  |
|        |                 |        | 10.0              | 109 | 108 | 108 | 107 | 108 | 107 | 107 | 106 | 106 | 105 | 105 | 104 | 104 | 103 | 103 | 103 | 100 |

