

屋内照明器具特性

品番 (品名)	LGC45807														
光源	LED6500_70_4500 x1 4500.0 lm														
管理番号	K0157517(0)DB1														
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	11%	床	10%				10%				10%				10%				0%	
下方光束	89%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	26	44	36	30	25	22
	中	0.6	0.8	63	51	42	36	60	49	41	36	56	47	40	35	52	44	38	34	31
	否	0.56	1.0	69	57	49	43	66	56	48	43	62	53	46	41	58	50	45	40	36
			1.25	75	64	56	50	72	63	55	49	67	59	53	48	63	56	51	46	42
下方投影面積	cm ²		1.5	79	69	62	56	76	67	60	55	71	64	58	53	67	60	55	51	47
等価発光面積	cm ²		2.0	84	76	69	64	82	74	68	63	77	70	65	60	72	67	62	58	54
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	79	73	68	80	75	70	66	75	71	67	63	59
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62
1.5m	1.95m	1.94m	4.0	94	89	84	80	91	87	82	78	86	82	79	75	81	78	75	72	67
2	2.57	2.56	5.0	96	92	88	84	93	89	86	82	88	85	82	79	84	81	78	76	70
2.5	3.13	3.13	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	75
3	3.76	3.75	10.0	101	98	96	93	98	96	94	91	93	91	89	88	88	87	85	84	78

