

屋内照明器具特性	
品番 (品名)	LGB16738
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184429 (0) DR 1
BZ分類	BZ1

器具効率			66 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %					
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
					床	10 %				10 %				10 %				10 %				0 %					
上方光束			1 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束			65 %																								
保守率			良 中 否	0.67	0.6	51	46	43	41	51	46	43	41	50	46	43	41	49	45	43	41	40					
				0.63	0.8	56	51	48	46	55	51	48	46	54	50	48	46	53	50	47	46	45					
				0.56	1.0	59	55	52	50	58	54	52	50	57	53	51	49	55	53	51	49	48					
					1.25	61	58	55	53	60	57	55	53	59	56	54	52	58	55	53	52	51					
下方投影面積			c m ²	1.5	63	60	57	55	62	59	57	55	60	58	56	54	59	57	55	54	53						
等価発光面積				c m ²	2.0	65	62	60	58	64	62	60	58	62	60	59	57	61	59	58	57	55					
取付 高さ	器具間隔最大限			2.5	66	64	62	60	65	63	61	60	64	62	60	59	62	61	60	58	57						
	横方向 (A)		縦方向 (B)	3.0	67	65	63	62	66	64	63	61	64	63	62	61	63	62	61	60	58						
H m	0.69 H m		0.69 H m	4.0	68	66	65	64	67	66	65	63	66	64	63	62	64	63	62	61	60						
				5.0	69	67	66	65	68	67	66	65	66	65	64	64	65	64	63	62	61						
				7.0	69	68	68	67	69	68	67	66	67	66	66	65	65	65	64	64	62						
				10.0	70	69	69	68	69	68	68	67	67	67	66	66	66	65	65	65	63						

