

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGC58200                     |  |  |  |  |  |  |  |  |  |
| 光源      | LED6200_70_5499 x1 5499.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0181800(0)DR1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ6/0.7/BZ5                  |  |  |  |  |  |  |  |  |  |

|        |                  |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|--------|------------------|---------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 器具効率   | 100%             | 天井      | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |      |
|        | 上方光束             |         | 25%              | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0%   |
|        | 下方光束             |         | 75%              |      | 床    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      | ZCM  |      |
| 保守率    | 良                | 0.63    | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |
|        | 中                | 0.6     | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |
|        | 否                | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |
|        | 0.56             | 0.56    | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |
| 下方投影面積 | c m <sup>2</sup> |         | 1.25             | 73   | 62   | 55   | 49   | 69   | 60   | 53   | 47   | 62   | 55   | 49   | 44   | 56   | 50   | 45   | 41   | 35   |      |
|        | 等価発光面積           |         | c m <sup>2</sup> | 1.5  | 77   | 67   | 60   | 54   | 73   | 64   | 58   | 52   | 66   | 59   | 54   | 49   | 60   | 54   | 49   | 46   | 39   |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 86   | 79   | 73   | 68   | 82   | 76   | 70   | 66   | 74   | 69   | 65   | 61   | 68   | 64   | 60   | 57   | 49   |      |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 88   | 82   | 77   | 72   | 84   | 79   | 74   | 70   | 77   | 72   | 69   | 65   | 70   | 66   | 63   | 60   | 53   |      |
| 1.5m   | 2.01m            | 1.96m   | 4.0              | 92   | 87   | 82   | 78   | 88   | 83   | 79   | 76   | 80   | 77   | 73   | 70   | 73   | 70   | 68   | 65   | 57   |      |
| 2      | 2.64             | 2.57    | 5.0              | 94   | 90   | 86   | 82   | 90   | 86   | 83   | 79   | 82   | 79   | 76   | 74   | 75   | 73   | 70   | 68   | 60   |      |
| 2.5    | 3.3              | 3.21    | 7.0              | 96   | 93   | 90   | 87   | 92   | 89   | 87   | 84   | 85   | 82   | 80   | 78   | 77   | 76   | 74   | 72   | 63   |      |
| 3      | 3.92             | 3.82    | 10.0             | 98   | 96   | 93   | 91   | 94   | 92   | 90   | 88   | 87   | 85   | 83   | 82   | 79   | 78   | 77   | 75   | 66   |      |

