

屋内照明器具特性

品番 (品名)	L G W C 8 0 3 6 1									
光源	LED2700_70_265 x1					265.0 l m				
管理番号	K0171393 (0) DB 1									
B Z 分類	B Z 6 / 1.4 / B Z 5 / 1.8 / B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	51 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	49 %		室指数	照明率 (X 0.01)																Z C M
保守率	良 中 否 0.63 0.6 0.56	0.6	4.8	3.7	2.9	2.4	4.4	3.4	2.7	2.3	3.7	2.9	2.4	2.0	3.0	2.4	2.0	1.7	1.2	
		0.8	5.7	4.6	3.8	3.3	5.2	4.2	3.6	3.1	4.4	3.6	3.1	2.7	3.6	3.0	2.6	2.3	1.6	
		1.0	6.3	5.2	4.5	3.9	5.8	4.9	4.2	3.7	4.9	4.1	3.6	3.2	4.0	3.5	3.1	2.7	1.9	
		1.25	6.8	5.9	5.2	4.6	6.3	5.5	4.8	4.3	5.3	4.6	4.1	3.7	4.4	3.9	3.5	3.2	2.3	
下方投影面積	c m ²	1.5	7.2	6.4	5.7	5.1	6.7	5.9	5.3	4.8	5.6	5.0	4.5	4.2	4.6	4.2	3.8	3.5	2.5	
		2.0	7.8	7.0	6.4	5.9	7.2	6.5	6.0	5.5	6.1	5.6	5.1	4.8	5.0	4.6	4.3	4.1	2.9	
取付高さ	器具間隔最大限		2.5	8.1	7.5	6.9	6.4	7.5	6.9	6.4	6.0	6.3	5.9	5.5	5.2	5.3	4.9	4.7	4.4	3.2
	横方向 (A)	縦方向 (B)	3.0	8.4	7.8	7.3	6.9	7.7	7.2	6.8	6.4	6.5	6.2	5.8	5.5	5.4	5.2	4.9	4.7	3.4
H m	1.37 H m	1.29 H m	4.0	8.7	8.2	7.8	7.4	8.0	7.6	7.3	6.9	6.8	6.5	6.2	6.0	5.7	5.5	5.2	5.1	3.7
			5.0	8.9	8.5	8.1	7.8	8.2	7.9	7.6	7.3	7.0	6.7	6.5	6.3	5.8	5.6	5.5	5.3	3.9
			7.0	9.1	8.8	8.5	8.3	8.4	8.2	7.9	7.7	7.2	7.0	6.8	6.6	6.0	5.9	5.7	5.6	4.1
			10.0	9.3	9.0	8.8	8.6	8.6	8.4	8.2	8.1	7.4	7.2	7.1	6.9	6.2	6.1	6.0	5.9	4.3

