

屋内照明器具特性

品番 (品名)	LGWC80363									
光源	LED2700_70_175 x1					175.0 lm				
管理番号	K0171394(0)DB1									
BZ分類	BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		51%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		49%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	68	59	51	46	63	54	48	43	53	46	41	37	43	39	35	31	22	
	等価発光面積	c m ²		1.5	72	63	56	51	67	59	53	48	56	50	45	41	46	42	38	35	25
取付高さ		器具間隔最大限		2.0	78	70	64	59	72	65	60	55	60	55	51	47	50	46	43	40	29
	H m	横方向 (A)	縦方向 (B)	2.5	81	74	69	64	75	69	64	60	63	59	55	52	52	49	46	44	31
1.37H m		1.25H m	3.0	83	78	73	68	77	72	68	64	65	61	58	55	54	51	49	47	33	
4.0	87	82	78	74	80	76	72	69	68	65	62	60	57	54	52	50	36				
5.0	88	85	81	78	82	79	75	73	70	67	65	62	58	56	54	53	38				
7.0	91	88	85	82	84	82	79	77	72	70	68	66	60	58	57	56	40				
10.0	93	90	88	86	86	84	82	80	73	72	71	69	61	60	59	58	42				

