

屋内照明器具特性

品番 (品名)	LGD1200														
光源	LED6200_70_485 x1 485.0 l m														
管理番号	K0154574 (0) DB 1														
BZ分類	BZ4/0.9/BZ3														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	100 %																				
保守率	良 中 否	0.67	0.6	60	48	41	36	59	48	41	36	56	47	40	36	54	46	40	36	34	
		0.63	0.8	71	60	53	48	69	60	53	48	67	58	52	48	65	57	52	47	45	
		0.56	1.0	78	68	62	56	76	68	61	56	74	66	60	56	71	65	60	56	54	
			1.25	84	76	69	64	82	75	69	64	80	73	68	64	77	72	67	63	61	
下方投影面積	c m ²	1.5	88	80	75	70	86	79	74	70	84	78	73	69	81	76	72	69	66		
		2.0	93	87	82	78	92	86	81	78	89	84	80	77	86	82	79	76	74		
取付高さ	器具間隔最大限		2.5	96	91	87	83	95	90	86	83	92	88	85	82	90	86	83	81	79	
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	89	86	94	91	88	85	92	89	86	84	82	
H m	1.31H m	1.31H m	4.0	101	97	94	92	99	96	94	91	97	94	92	90	94	92	90	88	86	
			5.0	102	99	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89	
			7.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	95	94	92	
			10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	97	94	

