

屋内照明器具特性

品番 (品名)	LGD9001														
光源	LDA4L-H-E17/S/4 x1 440.0lm														
管理番号	K0187029(0)DB1														
BZ分類	BZ4/0.9/BZ3/1.1/BZ4/1.4/BZ3/1.8/BZ4														

器具効率	65%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	65%	室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	3.9	3.2	2.7	2.4	3.9	3.2	2.7	2.4	3.7	3.1	2.7	2.4	3.6	3.0	2.7	2.4	2.3
	中	0.63	0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0
	否	0.56	1.0	5.0	4.4	3.9	3.6	4.9	4.3	3.9	3.6	4.7	4.2	3.9	3.6	4.6	4.2	3.8	3.6	3.4
			1.25	5.4	4.8	4.4	4.1	5.3	4.8	4.4	4.1	5.1	4.7	4.3	4.0	4.9	4.6	4.3	4.0	3.9
下方投影面積		cm^2	1.5	5.6	5.1	4.7	4.4	5.5	5.1	4.7	4.4	5.3	4.9	4.6	4.4	5.2	4.8	4.6	4.3	4.2
等価発光面積		cm^2	2.0	6.0	5.5	5.2	4.9	5.9	5.5	5.2	4.9	5.7	5.4	5.1	4.8	5.5	5.2	5.0	4.8	4.6
取付高さ	器具間隔最大限		2.5	6.2	5.8	5.5	5.3	6.1	5.7	5.5	5.2	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.1	5.0
	横方向 (A)	縦方向 (B)	3.0	6.3	6.0	5.7	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.2
Hm	1.34Hm	1.34Hm	4.0	6.5	6.2	6.0	5.8	6.4	6.2	6.0	5.8	6.2	6.0	5.9	5.7	6.0	5.9	5.8	5.6	5.5
			5.0	6.6	6.4	6.2	6.0	6.5	6.3	6.1	6.0	6.3	6.2	6.0	5.9	6.2	6.0	5.9	5.8	5.6
			7.0	6.7	6.6	6.4	6.3	6.6	6.5	6.4	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	5.9
			10.0	6.8	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.5	6.5	6.4	6.3	6.4	6.3	6.3	6.2	6.0

