

屋内照明器具特性	
品番 (品名)	XLGB1601
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0176229 (0) DR 1
BZ分類	BZ5

器具効率		53 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z CM																				
保守率		良 中 否	0.67	0.6	30	24	20	17	29	24	20	17	28	23	19	17	27	22	19	17	15				
			0.63	0.8	35	29	25	22	35	29	25	22	33	28	25	22	31	27	24	22	20				
			0.56	1.0	39	33	29	26	38	33	29	26	36	32	28	26	34	31	28	25	24				
				1.25	42	37	33	30	41	36	33	30	39	35	32	29	37	34	31	29	27				
下方投影面積		cm ²	1.5	44	39	36	33	43	39	35	33	41	38	35	32	39	36	34	32	30					
等価発光面積			2.0	47	43	40	37	46	42	39	37	44	41	38	36	42	40	38	36	34					
取付 高さ	器具間隔最大限			2.5	49	46	43	40	48	45	42	40	46	43	41	39	44	42	40	38	37				
	横方向 (A)		縦方向 (B)	3.0	50	47	45	43	49	46	44	42	47	45	43	41	45	44	42	40	39				
H m	0.82 H m		0.82 H m	4.0	52	49	47	46	51	49	47	45	49	47	46	44	47	46	44	43	41				
				5.0	53	51	49	48	52	50	48	47	50	48	47	46	48	47	46	45	43				
				7.0	54	53	51	50	53	52	50	49	51	50	49	48	49	49	48	47	45				
				10.0	55	54	53	52	54	53	52	51	52	51	51	50	50	50	49	49	46				

