

屋内照明器具特性

品番 (品名)	LGD9402	
光源	LLD2020LCE1 ×1	460.0 lm
管理番号	K0175560(0)DR1	
BZ分類	BZ1	

器具効率	96%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)																	ZCM	
保守率	良	0.67	0.6	79	73	69	66	78	73	69	66	77	72	69	66	76	71	68	66	65
	中	0.63	0.8	85	79	75	73	84	79	75	72	82	78	75	72	81	77	74	72	71
	否	0.56	1.0	88	83	80	77	87	83	79	77	86	82	79	76	84	81	78	76	75
下方投影面積	等価発光面積	cm ²	1.25	91	87	83	81	90	86	83	80	88	85	82	80	87	84	81	79	78
			1.5	93	89	86	84	92	88	86	83	90	87	85	83	89	86	84	82	80
取付高さ	器具間隔最大限		2.0	96	92	90	87	95	92	89	87	93	90	88	86	91	89	87	85	84
	横方向 (A)	縦方向 (B)	2.5	97	94	92	90	96	94	91	90	94	92	90	89	92	91	89	88	86
Hm	0.41Hm	0.41Hm	3.0	98	96	94	92	97	95	93	91	95	93	92	90	93	92	90	89	87
			4.0	100	98	96	94	98	97	95	94	96	95	94	93	94	93	92	91	89
			5.0	100	99	97	96	99	98	97	95	97	96	95	94	95	94	93	93	90
			7.0	101	100	99	98	100	99	98	97	98	97	96	96	96	95	95	94	92
			10.0	102	101	100	100	101	100	99	99	99	98	98	97	97	96	96	95	93

