

屋内照明器具特性

品番 (品名)	LGD9402				
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0lm				
管理番号	K0184654 (0) DR1				
BZ分類	BZ5/0.7/BZ4				

器具効率	81%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	0%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	81%																																																									
保守率	良 中 否	0.67	0.6	47	37	31	27	46	37	31	26	44	36	30	26	42	35	30	26	25																																						
		0.63	0.8	55	46	40	35	54	45	40	35	52	44	39	35	50	43	38	35	33																																						
		0.56	1.0	61	52	46	42	59	52	46	41	57	50	45	41	55	49	44	41	39																																						
			1.25	66	58	52	48	64	57	52	48	62	56	51	47	60	54	50	47	45																																						
下方投影面積	c m ²	1.5	69	62	57	52	68	61	56	52	65	60	55	52	63	58	54	51	49																																							
		2.0	73	68	63	59	72	67	62	59	70	65	61	58	67	64	60	57	55																																							
取付高さ	器具間隔最大限		2.5	76	71	67	64	75	70	66	63	72	69	65	62	70	67	64	62	60																																						
	横方向 (A)	縦方向 (B)	3.0	78	74	70	67	77	73	69	67	74	71	68	66	72	69	67	65	63																																						
H m	1.28H m	1.28H m	4.0	81	77	74	72	79	76	73	71	77	74	72	70	75	73	71	69	67																																						
			5.0	82	79	77	74	81	78	76	74	79	76	74	73	77	75	73	72	69																																						
			7.0	84	82	80	78	83	81	79	77	80	79	77	76	78	77	76	75	72																																						
			10.0	85	84	82	81	84	83	81	80	82	81	80	79	80	79	78	77	75																																						

