

屋内照明器具特性

品番 (品名)	LGD9405	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0175533(0)DR1	
BZ分類	BZ4/1.4/BZ3	

器具効率	64%	天井	80%				70%				50%				30%				0%					
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		64%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM			
保守率	良	0.67	0.6	3.8	3.1	2.6	2.3	3.7	3.0	2.6	2.3	3.6	3.0	2.6	2.3	3.5	2.9	2.5	2.3	2.1				
	中	0.63	0.8	4.5	3.8	3.3	3.0	4.4	3.8	3.3	3.0	4.2	3.7	3.3	3.0	4.1	3.6	3.2	3.0	2.8				
	否	0.56	1.0	4.9	4.3	3.9	3.5	4.8	4.3	3.8	3.5	4.7	4.2	3.8	3.5	4.5	4.1	3.7	3.5	3.3				
	下方投影面積	c m ²		1.25	5.3	4.8	4.3	4.0	5.2	4.7	4.3	4.0	5.0	4.6	4.3	4.0	4.9	4.5	4.2	4.0	3.8			
等価発光面積	c m ²		1.5	5.6	5.1	4.7	4.4	5.5	5.0	4.7	4.4	5.3	4.9	4.6	4.3	5.1	4.8	4.5	4.3	4.1				
	c m ²		2.0	5.9	5.5	5.2	4.9	5.8	5.4	5.1	4.9	5.6	5.3	5.0	4.8	5.5	5.2	5.0	4.8	4.6				
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.2	横方向 (A)		縦方向 (B)		6.0	5.7	5.4	5.2	5.8	5.6	5.3	5.1	5.7	5.4	5.3	5.1	4.9
	H _m	1.25H _m						1.25H _m																
H _m	1.25H _m		4.0	6.4	6.2	6.0	5.8	6.3	6.1	5.9	5.8	6.2	6.0	5.8	5.7	6.0	5.9	5.7	5.6	5.4				
			5.0	6.5	6.3	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6				
			7.0	6.6	6.5	6.4	6.2	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.1	6.1	6.0	5.8				
			10.0	6.7	6.6	6.5	6.4	6.6	6.5	6.5	6.4	6.5	6.4	6.3	6.3	6.3	6.3	6.2	6.2	6.0				

