

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 3
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0175765 (0) DR 1
B Z 分類	B Z 1

器具効率		28 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.67	0.6	26	25	24	24	26	25	24	24	25	25	24	24	25	24	24	24	23	
			0.63	0.8	27	26	25	25	27	26	25	25	26	26	25	25	26	25	25	25	24	
			0.56	1.0	27	27	26	26	27	26	26	25	27	26	26	25	27	26	26	25	25	
				1.25	28	27	27	26	28	27	27	26	27	27	26	26	27	26	26	26	25	
下方投影面積		c m ²	1.5	28	28	27	27	28	27	27	27	28	27	27	26	27	27	26	26	26		
			2.0	29	28	28	27	28	28	27	27	28	28	27	27	27	27	27	27	26		
等価発光面積		c m ²	2.5	29	28	28	28	29	28	28	28	28	28	27	27	28	27	27	27	26		
			3.0	29	29	28	28	29	28	28	28	28	28	28	27	28	28	27	27	27		
H m	0.76 H m		0.76 H m	4.0	29	29	29	28	29	29	28	28	28	28	28	28	28	28	27	27		
				5.0	29	29	29	29	29	29	29	28	28	28	28	28	28	28	28	27		
				7.0	29	29	29	29	29	29	29	29	29	28	28	28	28	28	28	27		
				10.0	30	29	29	29	29	29	29	29	29	29	28	28	28	28	28	27		

