

屋内照明器具特性

品番 (品名)	L G W 8 0 3 6 4									
光源	LED2700_70_265 ×1					265.0 l m				
管理番号	K0171393 (0) DB 1									
B Z 分類	B Z 6 / 1.4 / B Z 5 / 1.8 / B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		51 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		49 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0.01)																			Z C M	
保守率	良	0.63	0.6	48	37	29	24	44	34	27	23	37	29	24	20	30	24	20	17	12	
	中	0.6	0.8	57	46	38	33	52	42	36	31	44	36	31	27	36	30	26	23	16	
	否	0.56	1.0	63	52	45	39	58	49	42	37	49	41	36	32	40	35	31	27	19	
			1.25	68	59	52	46	63	55	48	43	53	46	41	37	44	39	35	32	23	
下方投影面積			c m ²	1.5	72	64	57	51	67	59	53	48	56	50	45	42	46	42	38	35	25
	等価発光面積		c m ²	2.0	78	70	64	59	72	65	60	55	61	56	51	48	50	46	43	41	29
取付高さ	器具間隔最大限			2.5	81	75	69	64	75	69	64	60	63	59	55	52	53	49	47	44	32
	横方向 (A)	縦方向 (B)		3.0	84	78	73	69	77	72	68	64	65	62	58	55	54	52	49	47	34
H m	1.37 H m	1.29 H m		4.0	87	82	78	74	80	76	73	69	68	65	62	60	57	55	52	51	37
				5.0	89	85	81	78	82	79	76	73	70	67	65	63	58	56	55	53	39
				7.0	91	88	85	83	84	82	79	77	72	70	68	66	60	59	57	56	41
				10.0	93	90	88	86	86	84	82	81	74	72	71	69	62	61	60	59	43

