

屋内照明器具特性	
品番 (品名)	LGB15393
光源	LLD4000MLCE1 ×1 845.0 lm
管理番号	K0175764 (0) DR 1
BZ分類	BZ1

器具効率	27 % 上方光束 0 % 下方光束 27 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		壁	10 %				10 %				10 %				10 %				0 %
		床	照明率 (X0.01)				Z CM												
保守率	良 0.67	室指数	0.6	25	24	23	23	25	24	23	23	24	24	23	23	24	23	23	22
	中 0.63		0.8	26	25	24	24	25	25	24	24	25	24	24	24	25	24	24	23
	否 0.56		1.0	26	25	25	24	26	25	25	24	26	25	25	24	25	25	24	24
			1.25	27	26	25	25	26	26	25	25	26	26	25	25	26	25	25	24
下方投影面積 等価発光面積	cm ²		1.5	27	26	26	25	27	26	26	25	26	26	26	25	26	26	25	25
	cm ²		2.0	27	27	26	26	27	27	26	26	27	26	26	26	26	26	25	25
			2.5	28	27	27	26	27	27	27	26	27	27	26	26	26	26	26	25
			3.0	28	27	27	27	27	27	27	27	27	27	26	26	27	26	26	25
取付高さ	器具間隔最大限		4.0	28	28	27	27	28	27	27	27	27	27	27	27	27	27	26	26
H m	横方向 (A)	縦方向 (B)	5.0	28	28	28	27	28	28	27	27	27	27	27	27	27	27	26	26
	0.76 H m	0.76 H m	7.0	28	28	28	28	28	28	28	27	27	27	27	27	27	27	27	26
			10.0	28	28	28	28	28	28	28	28	27	27	27	27	27	27	27	26

