

屋内照明器具特性

品番 (品名)	LGS3020V	
光源	LED3500_70_715 ×1	715.0 1m
管理番号	K0161680(0)DR1	
BZ分類	BZ1/1.1/BZ2/8.5/BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	0.6	73	64	59	55	72	64	58	55	70	63	58	55	68	62	58	55	53
	中 0.63		0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	66	63	61
	否 0.56		1.0	85	78	73	69	84	77	73	69	82	76	72	69	80	75	71	68	67
下方投影面積 等価発光面積	cm ²	cm ²	1.25	90	83	78	75	88	82	78	75	86	81	77	74	84	80	76	74	72
			1.5	93	87	83	79	91	86	82	79	89	85	81	78	87	83	80	77	76
取付高さ	器具間隔最大限		2.5	99	95	92	89	97	94	91	88	95	92	90	87	93	90	88	86	84
	横方向 (A)	縦方向 (B)	3.0	100	97	94	92	99	96	93	91	97	94	92	90	94	92	90	89	87
Hm	0.45Hm	0.45Hm	4.0	102	100	97	95	101	99	96	95	99	97	95	93	96	95	93	92	90
			5.0	103	101	99	98	102	100	98	97	100	98	97	95	98	96	95	94	91
			7.0	105	103	102	100	103	102	101	99	101	100	99	98	99	98	97	96	94
			10.0	106	105	103	102	104	103	102	102	102	101	100	100	100	99	99	98	95

