

|          |                             |
|----------|-----------------------------|
| 屋内照明器具特性 |                             |
| 品番 (品名)  | XAD3 2 1 0 L                |
| 光源       | LED2700_70_700 ×1 700.0 l m |
| 管理番号     | K0165460 ( 0 ) DB 1         |
| B Z 分類   | BZ4 / 0.7 / BZ3             |

|        |                                     |           |               |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    |     |    |
|--------|-------------------------------------|-----------|---------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|-----|----|
| 器具効率   | 100 %                               | 天井        | 80 %          |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 % |    |
|        |                                     | 壁         | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 % |    |
| 上方光束   | 0 %                                 | 床         | 10 %          |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 % |    |
| 下方光束   | 100 %                               | 室指数       | 照明率 ( X0.01 ) |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.67<br>0.63<br>0.56 | 0.6       | 61            | 50  | 43  | 38  | 60   | 50  | 43  | 38  | 58   | 49  | 42  | 38  | 56   | 48  | 42 | 38 | 36  |    |
|        |                                     | 0.8       | 72            | 62  | 55  | 50  | 71   | 61  | 55  | 50  | 68   | 60  | 54  | 50  | 66   | 59  | 53 | 49 | 47  |    |
|        |                                     | 1.0       | 79            | 70  | 63  | 58  | 77   | 69  | 63  | 58  | 75   | 68  | 62  | 58  | 73   | 66  | 61 | 57 | 55  |    |
|        |                                     | 1.25      | 85            | 77  | 71  | 66  | 83   | 76  | 70  | 66  | 81   | 74  | 69  | 65  | 78   | 73  | 68 | 65 | 63  |    |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5       | 89            | 81  | 76  | 71  | 87   | 81  | 75  | 71  | 84   | 79  | 74  | 71  | 82   | 77  | 73 | 70 | 68  |    |
|        |                                     | 2.0       | 94            | 88  | 83  | 79  | 92   | 87  | 82  | 79  | 90   | 85  | 81  | 78  | 87   | 83  | 80 | 77 | 75  |    |
| 取付高さ   | 器具間隔最大限                             |           | 2.5           | 97  | 92  | 88  | 84   | 95  | 91  | 87  | 84   | 93  | 89  | 86  | 83   | 90  | 87 | 84 | 82  | 79 |
|        | 横方向 ( A )                           | 縦方向 ( B ) | 3.0           | 99  | 94  | 91  | 88   | 97  | 93  | 90  | 87   | 95  | 91  | 89  | 86   | 92  | 90 | 87 | 85  | 83 |
| H m    | 1.24 H m                            | 1.24 H m  | 4.0           | 101 | 98  | 95  | 92   | 100 | 97  | 94  | 92   | 97  | 95  | 92  | 90   | 95  | 93 | 91 | 89  | 87 |
|        |                                     |           | 5.0           | 103 | 100 | 98  | 95   | 101 | 99  | 97  | 95   | 99  | 97  | 95  | 93   | 96  | 95 | 93 | 92  | 89 |
|        |                                     |           | 7.0           | 104 | 102 | 100 | 99   | 103 | 101 | 100 | 98   | 101 | 99  | 98  | 96   | 98  | 97 | 96 | 95  | 92 |
|        |                                     |           | 10.0          | 105 | 104 | 103 | 102  | 104 | 103 | 102 | 101  | 102 | 101 | 100 | 99   | 100 | 99 | 98 | 97  | 94 |

