

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | LGS3300V          |  |          |  |  |
| 光源      | LED3500_70_710 x2 |  | 710.0 lm |  |  |
| 管理番号    | K0157851(0)DB1    |  |          |  |  |
| BZ分類    | BZ4               |  |          |  |  |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |    |     |    |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|-----|----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |    |    |     | 0% |     |    |
|        | 上方光束            |         | 0%   | 壁   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 70 | 50  | 30 | 10  | 0% |
|        | 下方光束            |         | 100% |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |    | ZCM |    |
| 保守率    | 良               | 0.67    | 0.6  | 59  | 48  | 40  | 35  | 58  | 47  | 40  | 35  | 56  | 46  | 39  | 35  | 54 | 45 | 39  | 35 | 33  |    |
|        | 中               | 0.63    | 0.8  | 70  | 59  | 51  | 46  | 68  | 58  | 51  | 46  | 66  | 57  | 51  | 46  | 63 | 56 | 50  | 46 | 44  |    |
|        | 否               | 0.56    | 1.0  | 76  | 67  | 59  | 54  | 75  | 66  | 59  | 54  | 72  | 64  | 58  | 54  | 70 | 63 | 57  | 53 | 51  |    |
|        |                 |         | 1.25 | 82  | 74  | 67  | 62  | 81  | 73  | 67  | 62  | 78  | 71  | 66  | 61  | 75 | 69 | 65  | 61 | 59  |    |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 86  | 79  | 72  | 68  | 85  | 78  | 72  | 67  | 82  | 76  | 71  | 67  | 79 | 74 | 70  | 66 | 64  |    |
|        | 等価発光面積          |         | 2.0  | 92  | 85  | 80  | 76  | 90  | 84  | 79  | 75  | 88  | 82  | 78  | 75  | 85 | 81 | 77  | 74 | 71  |    |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 95  | 90  | 85  | 81  | 94  | 89  | 84  | 81  | 91  | 87  | 83  | 80  | 88 | 85 | 82  | 79 | 76  |    |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 97  | 93  | 89  | 85  | 96  | 92  | 88  | 85  | 93  | 90  | 86  | 83  | 91 | 88 | 85  | 82 | 80  |    |
| Hm     | 1.21Hm          | 1.22Hm  | 4.0  | 100 | 96  | 93  | 90  | 99  | 95  | 92  | 90  | 96  | 93  | 91  | 88  | 94 | 91 | 89  | 87 | 85  |    |
|        |                 |         | 5.0  | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 93  | 91  | 95 | 93 | 92  | 90 | 87  |    |
|        |                 |         | 7.0  | 104 | 101 | 99  | 98  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 97 | 96 | 95  | 93 | 91  |    |
|        |                 |         | 10.0 | 105 | 103 | 102 | 101 | 104 | 102 | 101 | 100 | 101 | 100 | 99  | 98  | 99 | 98 | 97  | 96 | 93  |    |

