

# 屋内照明器具特性

|         |                     |          |  |
|---------|---------------------|----------|--|
| 品番 (品名) | LGS3520N            |          |  |
| 光源      | LED5000_70_725 ×1   | 725.0 1m |  |
| 管理番号    | K0161680(0)DR1      |          |  |
| BZ分類    | BZ1/1.1/BZ2/8.5/BZ1 |          |  |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |
| 保守率    | 良 0.67          | 0.6     | 73   | 64  | 59  | 55  | 72  | 64  | 58  | 55  | 70  | 63  | 58  | 55  | 68  | 62  | 58 | 55 | 53 |     |
|        | 中 0.63          | 0.8     | 80   | 72  | 67  | 63  | 79  | 72  | 67  | 63  | 77  | 71  | 66  | 63  | 75  | 70  | 66 | 63 | 61 |     |
|        | 否 0.56          | 1.0     | 85   | 78  | 73  | 69  | 84  | 77  | 73  | 69  | 82  | 76  | 72  | 69  | 80  | 75  | 71 | 68 | 67 |     |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 90   | 83  | 78  | 75  | 88  | 82  | 78  | 75  | 86  | 81  | 77  | 74  | 84  | 80  | 76 | 74 | 72 |     |
|        |                 | 1.5     | 93   | 87  | 83  | 79  | 91  | 86  | 82  | 79  | 89  | 85  | 81  | 78  | 87  | 83  | 80 | 77 | 76 |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 96   | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 93  | 89  | 86  | 84  | 91  | 88  | 85 | 83 | 81 |     |
|        |                 | 2.5     | 99   | 95  | 92  | 89  | 97  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 90  | 88 | 86 | 84 |     |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 100 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 94  | 92 | 90 | 89 | 87  |
|        | 横方向 (A)         | 縦方向 (B) | 4.0  | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 95  | 99  | 97  | 95  | 93  | 96  | 95 | 93 | 92 | 90  |
| Hm     | 0.45Hm          | 0.45Hm  | 5.0  | 103 | 101 | 99  | 98  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 96 | 95 | 94 | 91  |
|        |                 |         | 7.0  | 105 | 103 | 102 | 100 | 103 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99  | 98 | 97 | 96 | 94  |
|        |                 |         | 10.0 | 106 | 105 | 103 | 102 | 104 | 103 | 102 | 102 | 102 | 101 | 100 | 100 | 100 | 99 | 99 | 98 | 95  |

