

屋内照明器具特性	
品番 (品名)	LGS9001
光源	LLD40402CQ1 (KAKUSAN) ×1      860.0 1m
管理番号	K0184322 (0) DR1
BZ分類	BZ4

器具効率	71%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	4.2	3.4	2.8	2.5	4.1	3.3	2.8	2.5	3.9	3.3	2.8	2.5	3.8	3.2	2.8	2.4	2.3	
	中	0.63	0.8	4.9	4.1	3.6	3.2	4.8	4.1	3.6	3.2	4.6	4.0	3.6	3.2	4.5	3.9	3.5	3.2	3.1	
	否	0.56	1.0	5.4	4.7	4.2	3.8	5.3	4.6	4.1	3.8	5.1	4.5	4.1	3.8	4.9	4.4	4.0	3.7	3.6	
	下方投影面積	c m <sup>2</sup>		1.25	5.8	5.2	4.7	4.3	5.7	5.1	4.7	4.3	5.5	5.0	4.6	4.3	5.3	4.9	4.5	4.2	4.1
等価発光面積	c m <sup>2</sup>		1.5	6.1	5.5	5.1	4.7	6.0	5.5	5.0	4.7	5.8	5.3	5.0	4.7	5.6	5.2	4.9	4.6	4.5	
	c m <sup>2</sup>		2.0	6.5	6.0	5.6	5.3	6.4	5.9	5.6	5.3	6.2	5.8	5.5	5.2	6.0	5.7	5.4	5.2	5.0	
取付高さ	器具間隔最大限		2.5	6.7	6.3	6.0	5.7	6.6	6.2	5.9	5.6	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	5.3	
	横方向 (A)	縦方向 (B)	3.0	6.9	6.5	6.2	6.0	6.8	6.4	6.2	5.9	6.6	6.3	6.1	5.8	6.4	6.2	6.0	5.8	5.6	
H m	1.23 H m	1.23 H m	4.0	7.1	6.8	6.6	6.3	7.0	6.7	6.5	6.3	6.8	6.6	6.4	6.2	6.6	6.4	6.3	6.1	5.9	
			5.0	7.2	7.0	6.8	6.6	7.1	6.9	6.7	6.5	6.9	6.7	6.6	6.4	6.7	6.6	6.5	6.3	6.1	
			7.0	7.3	7.2	7.0	6.9	7.2	7.1	6.9	6.8	7.1	6.9	6.8	6.7	6.9	6.8	6.7	6.6	6.4	
			10.0	7.4	7.3	7.2	7.1	7.3	7.2	7.1	7.0	7.2	7.1	7.0	6.9	7.0	6.9	6.9	6.8	6.6	

