

# 屋内照明器具特性

|         |                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGS9500                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD2000CU1 x1 566.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0179100(0)DR1         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                    |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |         |         |                   |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|---------|-------------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 99%     | 天井      | 80%               |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |         |         | 壁                 | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 1%      | 反射率     | 10%               |      |      |     | 10% |      |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 98%     |         | 床                 | 10%  |      |     |     | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
|        |         | 室指数     | 照明率 ( X0.01 ) ZCM |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良       | 0.67    | 0.6               | 5.6  | 4.4  | 3.6 | 3.0 | 5.4  | 4.3 | 3.6 | 3.0 | 5.2 | 4.2 | 3.5 | 3.0 | 5.0 | 4.1 | 3.5 | 3.0 | 2.8 |
|        | 中       | 0.63    | 0.8               | 6.6  | 5.4  | 4.6 | 4.1 | 6.4  | 5.3 | 4.6 | 4.0 | 6.1 | 5.2 | 4.5 | 4.0 | 5.9 | 5.1 | 4.5 | 4.0 | 3.8 |
|        | 否       | 0.56    | 1.0               | 7.2  | 6.1  | 5.4 | 4.8 | 7.1  | 6.1 | 5.3 | 4.8 | 6.8 | 5.9 | 5.2 | 4.7 | 6.5 | 5.7 | 5.2 | 4.7 | 4.5 |
|        |         |         | 1.25              | 7.8  | 6.8  | 6.1 | 5.5 | 7.6  | 6.7 | 6.1 | 5.5 | 7.3 | 6.6 | 5.9 | 5.5 | 7.0 | 6.4 | 5.8 | 5.4 | 5.2 |
| 下方投影面積 |         |         | 1.5               | 8.2  | 7.3  | 6.6 | 6.1 | 8.0  | 7.2 | 6.6 | 6.1 | 7.7 | 7.0 | 6.5 | 6.0 | 7.4 | 6.8 | 6.3 | 5.9 | 5.7 |
| 等価発光面積 |         |         | 2.0               | 8.8  | 8.0  | 7.4 | 6.9 | 8.6  | 7.9 | 7.4 | 6.9 | 8.3 | 7.7 | 7.2 | 6.8 | 8.0 | 7.5 | 7.1 | 6.7 | 6.4 |
| 取付高さ   | 器具間隔最大限 |         | 2.5               | 9.1  | 8.5  | 8.0 | 7.5 | 9.0  | 8.4 | 7.9 | 7.4 | 8.6 | 8.1 | 7.7 | 7.3 | 8.3 | 7.9 | 7.6 | 7.2 | 7.0 |
|        | 横方向 (A) | 縦方向 (B) | 3.0               | 9.4  | 8.8  | 8.3 | 7.9 | 9.2  | 8.7 | 8.2 | 7.9 | 8.9 | 8.5 | 8.1 | 7.7 | 8.6 | 8.2 | 7.9 | 7.6 | 7.3 |
| Hm     | 1.29Hm  | 1.29Hm  | 4.0               | 9.7  | 9.2  | 8.9 | 8.5 | 9.5  | 9.1 | 8.8 | 8.4 | 9.2 | 8.9 | 8.6 | 8.3 | 8.9 | 8.7 | 8.4 | 8.1 | 7.9 |
|        |         |         | 5.0               | 9.9  | 9.5  | 9.2 | 8.9 | 9.7  | 9.4 | 9.1 | 8.8 | 9.4 | 9.1 | 8.9 | 8.6 | 9.2 | 8.9 | 8.7 | 8.5 | 8.2 |
|        |         |         | 7.0               | 10.1 | 9.8  | 9.6 | 9.3 | 10.0 | 9.7 | 9.5 | 9.2 | 9.7 | 9.5 | 9.3 | 9.1 | 9.4 | 9.2 | 9.1 | 8.9 | 8.6 |
|        |         |         | 10.0              | 10.3 | 10.1 | 9.9 | 9.7 | 10.1 | 9.9 | 9.8 | 9.6 | 9.9 | 9.7 | 9.6 | 9.4 | 9.6 | 9.5 | 9.3 | 9.2 | 8.9 |

