

屋内照明器具特性

品番 (品名)	LRD9 2 0 1	
光源	LLD4000LCB1 ×1	845.0 l m
管理番号	K0175981 (0) DR 1	
B Z 分類	B Z 3	

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		47 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.63	0.6	2.9	2.4	2.1	1.9	2.9	2.4	2.1	1.9	2.8	2.4	2.1	1.9	2.7	2.3	2.0	1.9	1.8	
	中	0.6	0.8	3.4	3.0	2.7	2.4	3.4	2.9	2.6	2.4	3.3	2.9	2.6	2.4	3.2	2.8	2.6	2.4	2.3	
	否	0.56	1.0	3.8	3.3	3.0	2.8	3.7	3.3	3.0	2.8	3.6	3.2	3.0	2.8	3.5	3.2	2.9	2.8	2.7	
			1.25	4.0	3.6	3.4	3.2	4.0	3.6	3.3	3.1	3.8	3.5	3.3	3.1	3.7	3.5	3.3	3.1	3.0	
下方投影面積	c m ²		1.5	4.2	3.9	3.6	3.4	4.1	3.8	3.6	3.4	4.0	3.7	3.5	3.4	3.9	3.7	3.5	3.3	3.2	
	等価発光面積		c m ²	2.0	4.4	4.2	3.9	3.8	4.4	4.1	3.9	3.7	4.2	4.0	3.8	3.7	4.1	3.9	3.8	3.7	3.6
取付高さ	器具間隔最大限		2.5	4.6	4.3	4.1	4.0	4.5	4.3	4.1	4.0	4.4	4.2	4.0	3.9	4.3	4.1	4.0	3.9	3.8	
	横方向 (A)	縦方向 (B)	3.0	4.7	4.5	4.3	4.1	4.6	4.4	4.3	4.1	4.5	4.3	4.2	4.1	4.4	4.2	4.1	4.0	3.9	
H m	1.21 H m	1.21 H m	4.0	4.8	4.6	4.5	4.4	4.7	4.6	4.4	4.3	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.2	4.1	
			5.0	4.8	4.7	4.6	4.5	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.2	
			7.0	4.9	4.8	4.7	4.7	4.9	4.8	4.7	4.6	4.7	4.7	4.6	4.5	4.6	4.6	4.5	4.5	4.3	
			10.0	5.0	4.9	4.9	4.8	4.9	4.9	4.8	4.7	4.8	4.8	4.7	4.7	4.7	4.7	4.6	4.6	4.4	

