

屋内照明器具特性

品番 (品名)	L G W 4 6 1 4 6 Y	
光源	LED2700_70_20 x1	20.0 l m
管理番号	K0198963 (0) DB 1	
B Z 分類	BZ7 / 0.7 / BZ6 / 3.5 / BZ7	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %					
	上方光束 53 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
下方光束	47 %	床		10 %				10 %				10 %				10 %				0 %				
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.63	0.6	0.6	0.56	0.6	47	35	27	22	43	32	25	20	35	27	21	17	28	22	18	14	9	
	中	0.6	0.6	0.6	0.6	0.6	56	44	36	31	51	41	34	29	42	34	29	25	34	28	24	21	14	
	否	0.56	0.56	0.56	0.56	0.56	62	51	43	37	56	47	40	35	47	39	34	30	38	32	28	25	17	
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	2.5	3.0	67	57	49	43	61	53	46	41	51	44	39	35	41	36	32	29	20	
		2.0	2.5	3.0	4.0	5.0	71	61	54	48	65	57	50	45	54	48	43	39	44	39	35	32	22	
取付高さ	器具間隔最大限		H m	0.00 H m	0.20 H m	H m	2.5	79	72	66	61	73	67	61	57	61	56	52	48	49	46	43	40	27
	横方向 (A)	縦方向 (B)					3.0	82	75	70	65	75	70	65	60	63	59	55	51	51	48	45	43	29
H m	0.00 H m	0.20 H m	H m	H m	H m	4.0	85	80	75	71	78	74	69	66	66	62	59	56	54	51	49	46	32	
						5.0	87	82	78	74	80	76	72	69	67	64	61	59	55	53	51	49	49	34
H m	0.00 H m	0.20 H m	H m	H m	H m	7.0	89	86	82	79	82	79	76	74	69	67	65	63	57	55	54	52	36	
						10.0	91	88	86	84	84	82	80	78	71	69	68	66	59	58	56	55	39	

