

屋内照明器具特性

品番 (品名)	LRD9 100	
光源	LLD3020MLCB1 ×1	715.0 lm
管理番号	K0175979 (0) DR 1	
BZ分類	BZ1	

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	67 %	床	10 %				10 %				10 %				10 %				0 %				
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.56	0.6	55	51	48	46	55	51	48	46	54	50	48	46	53	50	48	46	45	
	中	0.6	0.6	0.6	0.6	59	56	53	51	59	55	53	51	58	55	52	51	57	54	52	51	50	
	否	0.56	1.0	0.56	0.56	62	59	56	54	61	58	56	54	60	57	55	54	59	57	55	54	53	
下方投影面積	等価発光面積	cm ²	cm ²	1.25	64	61	59	57	63	61	59	57	62	60	58	57	61	59	58	56	55		
				1.5	66	63	61	59	65	62	60	59	64	62	60	58	62	61	59	58	57		
取付高さ	器具間隔最大限		H _m	0.41H _m	H _m	0.41H _m	2.5	68	67	65	64	68	66	65	63	66	65	64	63	65	64	63	62
	横方向 (A)	縦方向 (B)					3.0	69	68	66	65	68	67	66	65	67	66	65	64	66	65	64	63
H _m	0.41H _m	0.41H _m	4.0	70	69	68	67	69	68	67	66	68	67	66	65	66	66	65	64	63			
			5.0	70	69	69	68	70	69	68	67	68	68	67	66	67	66	66	65	64			
H _m	0.41H _m	0.41H _m	7.0	71	70	70	69	70	70	69	68	69	68	68	67	67	67	67	66	65			
			10.0	72	71	70	70	71	70	70	69	69	69	69	68	68	68	68	67	65			

