

屋内照明器具特性

品番 (品名)	LRD9100														
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m														
管理番号	K0184515 (0) DR1														
BZ分類	BZ3														

器具効率	55%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	55%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	3.4	2.9	2.5	2.2	3.4	2.8	2.5	2.2	3.3	2.8	2.4	2.2	3.2	2.7	2.4	2.2	2.1		
		0.8	4.0	3.4	3.1	2.8	3.9	3.4	3.0	2.8	3.8	3.3	3.0	2.8	3.7	3.3	3.0	2.8	2.7		
		1.0	4.3	3.8	3.5	3.2	4.2	3.8	3.5	3.2	4.1	3.7	3.4	3.2	4.0	3.6	3.4	3.2	3.1		
		1.25	4.6	4.2	3.9	3.6	4.5	4.1	3.8	3.6	4.4	4.0	3.8	3.6	4.3	4.0	3.7	3.5	3.4		
下方投影面積 等価発光面積	c m ² c m ²	1.5	4.8	4.4	4.1	3.9	4.7	4.4	4.1	3.9	4.6	4.3	4.0	3.8	4.5	4.2	4.0	3.8	3.7		
		2.0	5.1	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.2	4.7	4.5	4.3	4.2	4.1		
		2.5	5.2	5.0	4.7	4.6	5.2	4.9	4.7	4.5	5.0	4.8	4.6	4.5	4.9	4.7	4.6	4.4	4.3		
取付高さ H m	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
	1.04 H m	1.04 H m	4.0	5.5	5.3	5.1	5.0	5.4	5.3	5.1	5.0	5.3	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7	
			5.0	5.6	5.4	5.3	5.2	5.5	5.4	5.2	5.1	5.4	5.2	5.1	5.0	5.2	5.1	5.0	5.0	4.8	
			7.0	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.3	5.3	5.2	5.1	5.0	
			10.0	5.7	5.7	5.6	5.5	5.7	5.6	5.5	5.5	5.5	5.5	5.4	5.4	5.4	5.4	5.3	5.3	5.1	

