

屋内照明器具特性

品番 (品名)	LRD9 1 0 2	
光源	LLD2020LCB1 ×1	460.0 1 m
管理番号	K0175964 (0) DR 1	
BZ分類	BZ1	

器具効率	74 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	74 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.63	0.6	0.6	61	56	53	51	60	56	53	51	59	55	53	51	58	55	53	51	50
	中 0.6	0.6	0.8	65	61	58	56	65	61	58	56	64	60	58	56	63	60	57	56	55
	否 0.56	0.6	1.0	68	64	62	60	68	64	62	60	66	63	61	59	65	63	61	59	58
下方投影面積 等価発光面積	c m ²	c m ²	1.25	71	67	65	63	70	67	65	63	69	66	64	62	67	65	63	62	61
			1.5	72	69	67	65	71	69	67	65	70	68	66	64	69	67	65	64	63
取付高さ	器具間隔最大限		2.5	75	73	72	70	75	73	71	70	73	72	70	69	72	70	69	68	67
	横方向 (A)	縦方向 (B)	3.0	76	74	73	72	75	74	72	71	74	72	71	70	72	71	70	69	68
H m	0.41 H m	0.41 H m	4.0	77	76	75	73	76	75	74	73	75	74	73	72	73	72	72	71	69
			5.0	78	77	76	75	77	76	75	74	75	74	74	73	74	73	72	72	70
			7.0	78	77	77	76	77	77	76	75	76	75	75	74	74	74	73	73	71
			10.0	79	78	78	77	78	77	77	76	76	76	75	75	75	74	74	74	72

