

屋内照明器具特性	
品番 (品名)	LRD9 2 0 1
光源	LLD2000LCB1 ×1 531.0 1 m
管理番号	K0175965 (0) DR 1
B Z 分類	B Z 3

器具効率	57 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		57 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0.01)																			Z C M	
保守率	良	0.63	0.6	3.5	2.9	2.5	2.2	3.5	2.9	2.5	2.2	3.3	2.8	2.5	2.2	3.2	2.8	2.5	2.2	2.1	
	中	0.6	0.8	4.1	3.6	3.2	2.9	4.0	3.5	3.2	2.9	3.9	3.4	3.1	2.9	3.8	3.4	3.1	2.9	2.8	
	否	0.56	1.0	4.5	4.0	3.6	3.3	4.4	3.9	3.6	3.3	4.3	3.9	3.6	3.3	4.1	3.8	3.5	3.3	3.2	
	下方投影面積	c m ²		1.25	4.8	4.4	4.0	3.8	4.7	4.3	4.0	3.8	4.6	4.2	4.0	3.7	4.4	4.1	3.9	3.7	3.6
等価発光面積	c m ²		1.5	5.0	4.6	4.3	4.1	4.9	4.6	4.3	4.0	4.8	4.5	4.2	4.0	4.6	4.4	4.2	4.0	3.9	
	c m ²		2.0	5.3	5.0	4.7	4.5	5.2	4.9	4.7	4.5	5.1	4.8	4.6	4.4	4.9	4.7	4.5	4.4	4.2	
取付高さ	器具間隔最大限		2.5	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.8	4.7	5.1	4.9	4.8	4.6	4.5	
	横方向 (A)	縦方向 (B)	3.0	5.6	5.3	5.1	5.0	5.5	5.3	5.1	4.9	5.3	5.2	5.0	4.9	5.2	5.1	4.9	4.8	4.7	
H m	1.21 H m	1.21 H m	4.0	5.7	5.5	5.4	5.2	5.6	5.5	5.3	5.2	5.5	5.3	5.2	5.1	5.4	5.2	5.1	5.0	4.9	
			5.0	5.8	5.6	5.5	5.4	5.7	5.6	5.5	5.3	5.6	5.5	5.4	5.3	5.4	5.3	5.3	5.2	5.0	
			7.0	5.9	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.5	5.5	5.4	5.3	5.2	
			10.0	5.9	5.9	5.8	5.7	5.9	5.8	5.7	5.7	5.7	5.7	5.6	5.6	5.6	5.6	5.5	5.5	5.3	

