

屋内照明器具特性	
品番 (品名)	LGB10841
光源	LLD3020CU1 ×1 615.0 lm
管理番号	K0179111 (0) DR1
BZ分類	BZ1

器具効率		75 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		75 %																							
保守率		良	0.67	0.6	64	60	57	55	64	60	57	55	63	59	57	55	62	59	57	55	54				
		中	0.63	0.8	68	64	62	60	68	64	62	60	67	64	61	60	66	63	61	60	59				
		否	0.56	1.0	71	67	65	63	70	67	65	63	69	66	64	63	68	66	64	62	62				
				1.25	73	70	68	66	72	69	67	66	71	69	67	65	70	68	66	65	64				
下方投影面積		c m ²		1.5	74	72	70	68	73	71	69	68	72	70	69	67	71	69	68	67	66				
等価発光面積		c m ²		2.0	76	74	72	71	75	73	72	70	74	72	71	70	72	71	70	69	68				
取付 高さ	器具間隔最大限			2.5	77	75	74	72	76	75	73	72	75	73	72	71	73	72	71	70	69				
	横方向 (A)		縦方向 (B)	3.0	78	76	75	74	77	75	74	73	75	74	73	72	74	73	72	71	70				
H m	0.33 H m		0.33 H m	4.0	78	77	76	75	78	77	76	75	76	75	74	74	75	74	73	73	71				
				5.0	79	78	77	76	78	77	76	76	77	76	75	75	75	74	74	73	72				
				7.0	80	79	78	77	79	78	77	77	77	77	76	76	76	75	75	74	72				
				10.0	80	79	79	78	79	79	78	78	77	77	77	76	76	76	75	75	73				

