

屋内照明器具特性

品番 (品名)	LRD9202			
光源	LLD2000LCB1 ×1 531.0 1m			
管理番号	K0175968(0)DR1			
BZ分類	BZ3			

器具効率	60%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束 下方光束	0% 60%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良 中 否	0.63	0.6	38	31	27	24	37	31	27	24	36	30	26	24	34	30	26	24	23
		0.6	0.8	44	38	34	31	43	38	34	31	42	37	33	31	40	36	33	31	29
		0.56	1.0	48	43	39	36	47	42	38	36	46	41	38	35	44	40	38	35	34
			1.25	51	47	43	40	50	46	43	40	49	45	42	40	47	44	42	40	38
下方投影面積 等価発光面積		c m ²	1.5	54	49	46	43	53	49	46	43	51	48	45	43	50	47	44	42	41
取付 高さ	器具間隔最大限		2.0	56	53	50	48	56	52	50	48	54	51	49	47	53	50	48	47	45
	横方向 (A)	縦方向 (B)	2.5	58	55	53	51	57	55	52	51	56	54	52	50	54	52	51	49	48
H m	1.21H m	1.21H m	3.0	59	57	55	53	59	56	54	53	57	55	53	52	56	54	53	51	50
			4.0	61	59	57	56	60	58	57	55	59	57	56	55	57	56	55	54	52
			5.0	62	60	59	57	61	60	58	57	59	58	57	56	58	57	56	55	54
			7.0	63	62	61	60	62	61	60	59	61	60	59	58	59	58	58	57	55
			10.0	63	63	62	61	63	62	61	61	61	61	60	59	60	59	59	58	57

