

屋内照明器具特性	
品番 (品名)	LRD9 2 0 2
光源	LLD2000LCB1 ×1                      531.0 l m
管理番号	K0175968 ( 0 ) DR 1
B Z 分類	B Z 3

器具効率	60 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	60 %	室指数	照明率 ( X 0 . 0 1 )																Z C M	
保守率	良	0.63	0.6	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.6	3.0	2.6	2.4	3.4	3.0	2.6	2.4	2.3
	中	0.6	0.8	4.4	3.8	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.3	3.1	4.0	3.6	3.3	3.1	2.9
	否	0.56	1.0	4.8	4.3	3.9	3.6	4.7	4.2	3.8	3.6	4.6	4.1	3.8	3.5	4.4	4.0	3.8	3.5	3.4
			1.25	5.1	4.7	4.3	4.0	5.0	4.6	4.3	4.0	4.9	4.5	4.2	4.0	4.7	4.4	4.2	4.0	3.8
下方投影面積			1.5	5.4	4.9	4.6	4.3	5.3	4.9	4.6	4.3	5.1	4.8	4.5	4.3	5.0	4.7	4.4	4.2	4.1
			2.0	5.6	5.3	5.0	4.8	5.6	5.2	5.0	4.8	5.4	5.1	4.9	4.7	5.3	5.0	4.8	4.7	4.5
取付高さ	器具間隔最大限		2.5	5.8	5.5	5.3	5.1	5.7	5.5	5.2	5.1	5.6	5.4	5.2	5.0	5.4	5.2	5.1	4.9	4.8
	横方向 (A)	縦方向 (B)	3.0	5.9	5.7	5.5	5.3	5.9	5.6	5.4	5.3	5.7	5.5	5.3	5.2	5.6	5.4	5.3	5.1	5.0
H m	1.21 H m	1.21 H m	4.0	6.1	5.9	5.7	5.6	6.0	5.8	5.7	5.5	5.9	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.2
			5.0	6.2	6.0	5.9	5.7	6.1	6.0	5.8	5.7	5.9	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.4
			7.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.8	5.7	5.5
			10.0	6.3	6.3	6.2	6.1	6.3	6.2	6.1	6.1	6.1	6.1	6.0	5.9	6.0	5.9	5.9	5.8	5.7

