

# 屋内照明器具特性

品番 (品名)	LRD9 2 0 2	
光源	LLD2000LCB1 ×1	531.0 lm
管理番号	K0175968 ( 0 ) DR 1	
BZ分類	BZ3	

器具効率	60%	天井	80%				70%				50%				30%				0%			
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		60%		床	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																				ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	
	等価発光面積																					
取付高さ	器具間隔最大限																					
	横方向 (A)	縦方向 (B)																				
H m	1.21 H m	1.21 H m																				
			4.0	5.0	6.0	7.0	8.0	10.0														
			5.0	6.0	7.0	8.0	10.0															
			7.0	8.0	10.0																	
			10.0																			

