

屋内照明器具特性

| | | |
|---------|----------------|----------|
| 品番 (品名) | LRD9202 | |
| 光源 | LLD2020LCB1 ×1 | 460.0 lm |
| 管理番号 | K0175971(0)DR1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 74% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 | | 0% | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 74% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 61 | 56 | 53 | 51 | 60 | 56 | 53 | 51 | 59 | 55 | 53 | 51 | 58 | 55 | 53 | 51 | 50 |
| | 中 | 0.6 | 0.8 | 65 | 61 | 58 | 56 | 65 | 61 | 58 | 56 | 64 | 60 | 58 | 56 | 63 | 60 | 57 | 56 | 55 |
| | 否 | 0.56 | 1.0 | 68 | 65 | 62 | 60 | 68 | 64 | 62 | 60 | 66 | 63 | 61 | 59 | 65 | 63 | 61 | 59 | 58 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 71 | 67 | 65 | 63 | 70 | 67 | 65 | 63 | 69 | 66 | 64 | 62 | 67 | 65 | 63 | 62 | 61 |
| | | | 1.5 | 72 | 69 | 67 | 65 | 71 | 69 | 67 | 65 | 70 | 68 | 66 | 64 | 69 | 67 | 65 | 64 | 63 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 74 | 72 | 70 | 68 | 73 | 71 | 69 | 68 | 72 | 70 | 69 | 67 | 71 | 69 | 68 | 67 | 65 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 75 | 73 | 72 | 70 | 75 | 73 | 71 | 70 | 73 | 72 | 70 | 69 | 72 | 70 | 69 | 68 | 67 |
| Hm | Hm | Hm | 3.0 | 76 | 74 | 73 | 72 | 75 | 74 | 72 | 71 | 74 | 72 | 71 | 70 | 72 | 71 | 70 | 69 | 68 |
| | | | 4.0 | 77 | 76 | 75 | 73 | 76 | 75 | 74 | 73 | 75 | 74 | 73 | 72 | 73 | 72 | 72 | 71 | 69 |
| | | | 5.0 | 78 | 77 | 76 | 75 | 77 | 76 | 75 | 74 | 75 | 74 | 74 | 73 | 74 | 73 | 72 | 72 | 70 |
| | | | 7.0 | 78 | 78 | 77 | 76 | 77 | 77 | 76 | 75 | 76 | 75 | 75 | 74 | 74 | 74 | 73 | 73 | 71 |
| | | | 10.0 | 79 | 78 | 78 | 77 | 78 | 77 | 77 | 76 | 76 | 76 | 75 | 75 | 75 | 74 | 74 | 74 | 72 |

