

屋内照明器具特性	
品番 (品名)	XLGB1635
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0176328 (0) DR 1
BZ分類	BZ4

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	50	40	34	29	49	39	33	29	46	38	33	29	44	37	32	28	26	
			0.63	0.8	59	50	44	39	58	49	43	39	55	47	42	38	52	46	41	37	35	
			0.56	1.0	65	57	51	46	64	56	50	46	60	54	49	45	58	52	48	44	42	
				1.25	70	63	57	53	69	62	56	52	65	60	55	51	62	58	54	50	48	
下方投影面積		cm ²	1.5	74	67	62	58	72	66	61	57	69	64	59	56	66	61	58	55	52		
			2.0	78	73	68	65	77	71	67	64	73	69	65	62	70	67	64	61	58		
等価発光面積		cm ²	2.5	81	76	72	69	79	75	71	68	76	72	69	67	73	70	67	65	62		
			3.0	83	79	75	72	81	77	74	71	78	75	72	70	75	72	70	68	65		
H _m	1.32 H _m		1.32 H _m	4.0	85	82	79	77	84	81	78	76	80	78	76	74	77	75	73	72	68	
				5.0	87	84	82	79	85	83	80	78	82	80	78	76	79	77	75	74	70	
				7.0	88	86	84	83	87	85	83	81	83	82	80	79	80	79	78	77	73	
				10.0	90	88	87	85	88	87	85	84	85	84	82	81	82	81	80	79	75	

