

# 屋内照明器具特性

品番 (品名)	XAD3 1 1 4 V				
光源	LED3500_70_600 x1		600.0 l m		
管理番号	K0165490 ( 0 ) DB 1				
B Z 分類	BZ4 / 0.7 / BZ3				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	61	50	43	37	60	49	42	37	58	48	42	37	56	47	41	37	35	
	中	0.63	0.8	72	61	54	49	70	61	54	49	68	59	53	49	65	58	53	49	47	
	否	0.56	1.0	78	69	62	57	77	68	62	57	74	67	61	57	72	65	60	56	54	
			1.25	84	76	70	65	83	75	69	65	80	74	68	64	78	72	68	64	62	
下方投影面積	c m <sup>2</sup>		1.5	88	81	75	70	87	80	75	70	84	78	73	70	81	76	72	69	67	
等価発光面積	c m <sup>2</sup>		2.0	93	87	82	78	92	86	82	78	89	84	80	77	87	83	79	76	74	
取付高さ	器具間隔最大限		2.5	96	91	87	83	95	90	86	83	92	88	85	82	90	86	83	81	79	
	横方向 (A)	縦方向 (B)	3.0	98	94	90	87	97	93	89	86	94	91	88	85	92	89	86	84	82	
H m	1.25 H m	1.25 H m	4.0	101	97	94	92	99	96	94	91	97	94	92	90	94	92	90	88	86	
			5.0	102	100	97	95	101	98	96	94	99	96	94	93	96	94	93	91	89	
			7.0	104	102	100	98	103	101	99	98	100	99	97	96	98	97	95	94	92	
			10.0	105	104	103	101	104	103	102	100	102	101	100	98	99	98	98	97	94	

