

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XAD1231V          |          |
| 光源      | LED3500_70_450 ×1 | 450.0 lm |
| 管理番号    | K0165463 (1) DB1  |          |
| BZ分類    | BZ1               |          |

|        |               |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%          | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        | 上方光束          |                 | 0%   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束   | 100%          | 床               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 室指数    | 照明率 ( X0.01 ) |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率    | 良             | 0.67            | 0.6  | 83  | 77  | 73  | 70  | 82  | 77  | 73  | 70  | 81  | 76  | 73  | 70  | 80  | 75  | 72  | 70  | 69  |
|        | 中             | 0.63            | 0.8  | 89  | 84  | 80  | 77  | 88  | 83  | 80  | 77  | 87  | 82  | 79  | 77  | 86  | 82  | 79  | 77  | 75  |
|        | 否             | 0.56            | 1.0  | 93  | 88  | 85  | 82  | 92  | 88  | 84  | 82  | 90  | 87  | 84  | 81  | 89  | 86  | 83  | 81  | 80  |
| 下方投影面積 | 等価発光面積        | cm <sup>2</sup> | 1.25 | 96  | 92  | 89  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 87  | 85  | 92  | 89  | 87  | 85  | 83  |
|        |               |                 | 1.5  | 98  | 94  | 91  | 89  | 97  | 94  | 91  | 89  | 95  | 92  | 90  | 88  | 94  | 91  | 89  | 87  | 86  |
| 取付高さ   | 器具間隔最大限       |                 | 2.5  | 102 | 100 | 97  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 96  | 94  | 93  | 91  |
|        | 横方向 (A)       | 縦方向 (B)         | 3.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 96  | 95  | 92  |
| Hm     | 0.40Hm        | 0.40Hm          | 4.0  | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 99  | 98  | 99  | 98  | 97  | 96  | 94  |
|        |               |                 | 5.0  | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95  |
|        |               |                 | 7.0  | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 100 | 99  | 97  |
|        |               |                 | 10.0 | 107 | 106 | 105 | 105 | 106 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 101 | 101 | 101 | 100 | 97  |

