

屋内照明器具特性

品番 (品名)	XAD1430V	
光源	LED3500_70_450 ×1	450.0 lm
管理番号	K0166801(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	壁	照明率 (X0.01)																ZCM	
下方光束	100%	床																		
保守率	良 中 否	0.67 0.63 0.56	室指数																	
						0.6	77	69	65	61	76	69	64	61	75	68	64	61	73	68
			0.8	85	78	73	70	84	77	73	70	82	76	72	69	80	75	72	69	68
			1.0	89	83	79	76	88	83	79	75	86	81	78	75	85	80	77	75	73
			1.25	93	88	84	81	92	87	83	81	90	86	83	80	88	85	82	80	78
			1.5	96	91	87	84	95	90	87	84	93	89	86	84	91	88	85	83	81
			2.0	99	95	92	90	98	94	92	89	96	93	90	88	94	91	89	87	86
			2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88
			3.0	102	99	97	95	101	99	96	95	99	97	95	93	97	95	94	92	90
			4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92
			5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	97	96	94
			7.0	106	105	103	102	105	104	102	101	102	101	100	100	100	99	98	96	96
			10.0	107	106	105	104	105	104	103	103	102	101	101	101	100	100	100	97	97

