

屋内照明器具特性	
品番 (品名)	LGB15336
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0190427 (0) DR 1
B Z 分類	BZ1

器具効率		81 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		81 %	室指数	照明率 (X0.01)																Z C M	
保守率		良	0.6	68	64	61	59	68	64	61	59	67	63	60	59	66	63	60	58	58	
		中	0.8	73	69	67	64	73	69	66	64	72	68	66	64	71	68	66	64	63	
		否	1.0	76	73	70	68	76	72	70	68	74	71	69	68	73	71	69	67	66	
			0.56	1.25	79	76	73	71	78	75	73	71	77	74	72	71	75	73	72	70	69
下方投影面積		c m ²	1.5	80	77	75	74	79	77	75	73	78	76	74	73	77	75	74	72	71	
等価発光面積		c m ²	2.0	82	80	78	77	81	79	78	76	80	78	77	76	78	77	76	75	74	
取付 高さ	器具間隔最大限		2.5	83	81	80	79	82	81	79	78	81	80	78	77	79	78	77	77	75	
	横方向 (A)	縦方向 (B)	3.0	84	82	81	80	83	82	81	80	82	80	79	79	80	79	78	78	76	
H m	0.41 H m	0.41 H m	4.0	85	84	83	82	84	83	82	81	82	82	81	80	81	80	80	79	77	
			5.0	86	85	84	83	85	84	83	82	83	82	82	81	81	81	80	80	78	
			7.0	86	86	85	84	85	85	84	84	84	83	83	82	82	82	81	81	79	
			10.0	87	86	86	85	86	85	85	85	84	84	83	83	82	82	82	82	80	

