

屋内照明器具特性

品番 (品名)	LGS9003														
光源	LLD4000LCB1 ×1 845.0 lm														
管理番号	K0179469(0)DR1														
BZ分類	BZ4/1.1/BZ3/3.5/BZ4														

器具効率	54%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (×0.01) ZCM																		
下方光束	54%																				
保守率	良 0.67 中 0.63 否 0.56	0.6	33	26	22	20	32	26	22	20	31	25	22	19	30	25	22	19	18		
		0.8	38	33	29	26	38	32	28	26	36	31	28	26	35	31	28	25	24		
		1.0	42	37	33	30	41	36	33	30	40	35	32	30	38	35	32	30	29		
		1.25	45	41	37	34	44	40	37	34	43	39	36	34	41	38	36	34	33		
下方投影面積	c m ²	1.5	47	43	40	37	46	43	40	37	45	42	39	37	43	41	38	36	35		
		2.0	50	47	44	42	49	46	44	41	48	45	43	41	46	44	42	40	39		
取付高さ	器具間隔最大限		2.5	52	49	46	44	51	48	46	44	49	47	45	44	48	46	44	43	42	
	横方向 (A)	縦方向 (B)	3.0	53	50	48	46	52	50	48	46	51	49	47	45	49	48	46	45	44	
H _m	1.29H _m	1.29H _m	4.0	54	52	51	49	54	52	50	49	52	51	49	48	51	50	48	47	46	
			5.0	55	54	52	51	55	53	52	50	53	52	51	50	52	51	50	49	47	
			7.0	56	55	54	53	56	54	53	52	54	53	52	52	53	52	51	51	49	
			10.0	57	56	55	55	56	56	55	54	55	54	54	53	54	53	53	52	50	

