

# 屋内照明器具特性

|         |                        |  |  |  |  |
|---------|------------------------|--|--|--|--|
| 品番 (品名) | LGS9003                |  |  |  |  |
| 光源      | LLD2000CU1 x1 566.0 lm |  |  |  |  |
| 管理番号    | K0178927(0)DR1         |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ3            |  |  |  |  |

|        |               |         |                 |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |     |
|--------|---------------|---------|-----------------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率   | 76%           | 天井      | 80%             |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |     |
|        | 上方光束          |         | 0%              | 反射率  | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束          |         | 76%             |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 ) |         |                 |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    | ZCM |
| 保守率    | 良             | 0.67    | 0.6             | 46   | 38 | 32  | 28  | 45 | 37 | 32  | 28  | 44 | 36 | 32  | 28  | 42 | 36 | 31  | 28 | 27 |     |
|        | 中             | 0.63    | 0.8             | 54   | 46 | 41  | 37  | 53 | 46 | 41  | 37  | 51 | 45 | 40  | 37  | 50 | 44 | 40  | 37 | 35 |     |
|        | 否             | 0.56    | 1.0             | 59   | 52 | 47  | 43  | 58 | 52 | 47  | 43  | 56 | 51 | 46  | 43  | 54 | 49 | 46  | 43 | 41 |     |
|        |               |         |                 | 1.25 | 64 | 58  | 53  | 49 | 63 | 57  | 52  | 49 | 61 | 56  | 52  | 49 | 59 | 54  | 51 | 48 | 47  |
| 下方投影面積 |               |         | cm <sup>2</sup> | 1.5  | 67 | 61  | 57  | 53 | 66 | 60  | 56  | 53 | 64 | 59  | 56  | 53 | 62 | 58  | 55 | 52 | 51  |
|        | 等価発光面積        |         | cm <sup>2</sup> | 2.0  | 71 | 66  | 62  | 59 | 70 | 65  | 62  | 59 | 68 | 64  | 61  | 58 | 66 | 63  | 60 | 58 | 56  |
| 取付高さ   | 器具間隔最大限       |         |                 | 2.5  | 73 | 69  | 66  | 63 | 72 | 68  | 65  | 63 | 70 | 67  | 64  | 62 | 68 | 66  | 63 | 61 | 60  |
|        | 横方向 (A)       | 縦方向 (B) |                 | 3.0  | 75 | 71  | 69  | 66 | 74 | 71  | 68  | 66 | 72 | 69  | 67  | 65 | 70 | 68  | 66 | 64 | 62  |
| Hm     | 1.23Hm        | 1.23Hm  |                 | 4.0  | 77 | 74  | 72  | 70 | 76 | 73  | 71  | 69 | 74 | 72  | 70  | 68 | 72 | 70  | 69 | 67 | 65  |
|        |               |         |                 | 5.0  | 78 | 76  | 74  | 72 | 77 | 75  | 73  | 71 | 75 | 73  | 72  | 70 | 73 | 72  | 70 | 69 | 67  |
|        |               |         |                 | 7.0  | 79 | 78  | 76  | 75 | 78 | 77  | 75  | 74 | 76 | 75  | 74  | 73 | 74 | 73  | 73 | 72 | 70  |
|        |               |         |                 | 10.0 | 80 | 79  | 78  | 77 | 79 | 78  | 77  | 76 | 77 | 76  | 76  | 75 | 76 | 75  | 74 | 74 | 71  |

