

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | LGS9003             |          |
| 光源      | LLD4000LCB1 ×1      | 845.0 lm |
| 管理番号    | K0179469(0)DR1      |          |
| BZ分類    | BZ4/1.1/BZ3/3.5/BZ4 |          |

|        |                 |         |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 54%             | 天井      | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        | 上方光束            |         | 0%              | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        | 下方光束            |         | 54%             |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     |
| 室指数    | 照明率 ( X0.01 )   |         |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率    | 良               | 0.67    | 0.6             | 3.3 | 2.6 | 2.2 | 2.0 | 3.2 | 2.6 | 2.2 | 2.0 | 3.1 | 2.5 | 2.2 | 1.9 | 3.0 | 2.5 | 2.2 | 1.9 | 1.8 |     |
|        | 中               | 0.63    | 0.8             | 3.8 | 3.3 | 2.9 | 2.6 | 3.8 | 3.2 | 2.8 | 2.6 | 3.6 | 3.1 | 2.8 | 2.6 | 3.5 | 3.1 | 2.8 | 2.5 | 2.4 |     |
|        | 否               | 0.56    | 1.0             | 4.2 | 3.7 | 3.3 | 3.0 | 4.1 | 3.6 | 3.3 | 3.0 | 4.0 | 3.5 | 3.2 | 3.0 | 3.8 | 3.5 | 3.2 | 3.0 | 2.9 |     |
|        |                 |         | 1.25            | 4.5 | 4.1 | 3.7 | 3.4 | 4.4 | 4.0 | 3.7 | 3.4 | 4.3 | 3.9 | 3.6 | 3.4 | 4.1 | 3.8 | 3.6 | 3.4 | 3.3 |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5             | 4.7 | 4.3 | 4.0 | 3.7 | 4.6 | 4.3 | 4.0 | 3.7 | 4.5 | 4.2 | 3.9 | 3.7 | 4.3 | 4.1 | 3.8 | 3.6 | 3.5 |     |
|        | 等価発光面積          |         | cm <sup>2</sup> | 2.0 | 5.0 | 4.7 | 4.4 | 4.2 | 4.9 | 4.6 | 4.4 | 4.1 | 4.8 | 4.5 | 4.3 | 4.1 | 4.6 | 4.4 | 4.2 | 4.0 | 3.9 |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 5.2 | 4.9 | 4.6 | 4.4 | 5.1 | 4.8 | 4.6 | 4.4 | 4.9 | 4.7 | 4.5 | 4.4 | 4.8 | 4.6 | 4.4 | 4.3 | 4.2 |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 5.3 | 5.0 | 4.8 | 4.6 | 5.2 | 5.0 | 4.8 | 4.6 | 5.1 | 4.9 | 4.7 | 4.5 | 4.9 | 4.8 | 4.6 | 4.5 | 4.4 |     |
| Hm     | 1.29Hm          | 1.29Hm  | 4.0             | 5.4 | 5.2 | 5.1 | 4.9 | 5.4 | 5.2 | 5.0 | 4.9 | 5.2 | 5.1 | 4.9 | 4.8 | 5.1 | 5.0 | 4.8 | 4.7 | 4.6 |     |
|        |                 |         | 5.0             | 5.5 | 5.4 | 5.2 | 5.1 | 5.5 | 5.3 | 5.2 | 5.0 | 5.3 | 5.2 | 5.1 | 5.0 | 5.2 | 5.1 | 5.0 | 4.9 | 4.7 |     |
|        |                 |         | 7.0             | 5.6 | 5.5 | 5.4 | 5.3 | 5.6 | 5.4 | 5.3 | 5.2 | 5.4 | 5.3 | 5.2 | 5.2 | 5.3 | 5.2 | 5.1 | 5.1 | 4.9 |     |
|        |                 |         | 10.0            | 5.7 | 5.6 | 5.5 | 5.5 | 5.6 | 5.6 | 5.5 | 5.4 | 5.5 | 5.4 | 5.4 | 5.3 | 5.4 | 5.3 | 5.3 | 5.2 | 5.0 |     |

