

屋内照明器具特性

品番 (品名)	LGS9003	
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 1 m	
管理番号	K0184331 (0) DR 1	
BZ分類	BZ1	

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	85 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	67	61	57	54	66	61	57	54	65	60	57	54	64	59	56	54	53	
	中	0.63	0.8	74	68	64	62	73	68	64	62	71	67	64	61	70	66	63	61	60	
	否	0.56	1.0	77	73	69	66	77	72	69	66	75	71	68	66	74	70	68	66	64	
下方投影面積 等価発光面積	c m ²	1.25	1.25	81	76	73	71	80	76	73	70	78	75	72	70	77	74	71	70	68	
		1.5	1.5	83	79	76	74	82	78	76	73	80	77	75	73	78	76	74	72	71	
取付高さ	器具間隔最大限		2.0	2.0	85	82	80	78	84	81	79	77	82	80	78	77	81	79	77	76	74
	H m	0.74 H m	2.5	2.5	87	84	82	80	86	83	81	80	84	82	80	79	82	81	79	78	76
H m		0.74 H m	3.0	3.0	88	86	84	82	87	85	83	82	85	83	82	81	83	82	81	80	78
	H m	0.74 H m	4.0	4.0	89	87	86	84	88	86	85	84	86	85	84	83	84	83	82	82	80
H m		0.74 H m	5.0	5.0	90	88	87	86	89	87	86	85	87	86	85	84	85	84	83	83	81
	H m	0.74 H m	7.0	7.0	91	89	89	88	90	89	88	87	88	87	86	85	86	85	85	84	82
H m		0.74 H m	10.0	10.0	91	90	90	89	90	89	89	88	88	88	87	87	86	86	86	85	83

